

Learning-based Face Synthesis for Pose-Robust Recognition from Single Image

Akshay Asthana¹ Conrad Sanderson² Tom Gedeon¹ Roland Goecke^{1,3}

¹ RSISE and DCS, Australian National University, Australia.

² NICTA and University of Queensland, Australia.

³ Faculty of Information Sciences and Engineering, University of Canberra, Australia.

aasthana@rsise.anu.edu.au , conradsand@ieee , tom.gedeon@anu.edu.au , roland.goecke@ieee.org

Supplementary Material

Table : RANK – 1 Recognition Rates

| Pose Variation | PCA based Approach | | MRH based Approach | |
|------------------|--------------------|---------------------|--------------------|---------------------|
| | Frontal | Frontal + Synthetic | Frontal | Frontal + Synthetic |
| -60° (bi subset) | 6% | 12% | 11% | 48% |
| -40° (bh subset) | 15% | 30% | 58% | 87% |
| -25° (bg subset) | 51% | 61.5% | 92.5% | 93% |
| -15° (bf subset) | 77.5% | 80.5% | 98% | 98% |
| +15° (be subset) | 64% | 73.5% | 98.5% | 98.5% |
| +25° (bd subset) | 39.5% | 52% | 86.5% | 95.5% |
| +40° (bc subset) | 14% | 30% | 54% | 74% |
| +60° (bb subset) | 4% | 14% | 14% | 32.5% |